

Terminal Tractor/Yard Spotter

Used Yard Spotter Vermont - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. These machines can tow numerous trailers in a train or snake-like formation. Certain tow tractors can transport helicopters and giant airplanes for the purpose of positioning inside and outside airport hangars and terminals. Tractive effort is how these machines transport loads. Tractive effort is the amount of traction a unit has on the ground. Heavier loads require more tractive effort compared to lighter loads. Based on this principle, the tow tractor works by lifting a part of the load it is towing while making sure the load's wheels remain on the ground. The hydraulic mast on the tow tractor is responsible for lifting the load. It produces downforce on the drive wheel underneath to increase the tractive effort. Traction allows the machine to deliver very large and heavy loads. Types of Tow Tractors Heavy-duty tow tractors and load carriers are two types of tow tractors. Load Carriers Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. The category that load carrier tow tractor models fall into includes forklift trucks, cranes and pallet jacks. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. This means that the load has already been on wheels or placed on a wheeled platform before transport. Wheeled platforms are called skates, trollies and bogies. The tow tractor joins to the trolley and functions similarly to a train locomotive. Typically, the tow tug features a steel coupling male-end that attaches to a female-end on the trolley's front. The back of the trolley has a male-end steel coupling that can then be used to attach multiple trollies onto a single tow tug, transporting all the trollies in a train-like formation. These machines can transport a variety of items in varying conditions. Different trolley types are on the market to facilitate better transportation customization. Trollies can connect together and are compatible. Since multiple trolley types can be utilized in a single train, there is flexibility. An additional benefit of operating with load carrier tow tractors as opposed to forklifts is the unobstructed view offered by a tow tractor, increasing the safety of work areas. Load carrier tow tractors transport trollies in a forward direction which decreases the safety concerns common with reverse forklift operations. This design is excellent for locations that have a high level of safety such as manufacturing locations and airports. Towing many items at once saves time and money compared to relying on forklifts to move single things. Tugs are simple to move and provide a safe transport option. The operator doesn't require a license, which is another benefit compared to forklifts. No license is necessary since these units do not lift loads up from the ground like cranes, and forklifts that require licensing. There are three kinds of load carrier tow tractor units to choose from; pedestrian, stand-in and rider-seated. Pedestrian Tow Tractors Pedestrian tow tractors go by many names including electric tow tractor, electric tug, or electric tugger. These units are walk-behind models that move wheeled loads. These compact machines are simple to use and can maneuver easily. Stand-in Tow Tractors The most common design for businesses that rely on horizontal manufacturing transport and order picking are stand-in tow tractors. Stand-in tow tractors feature a tinier footprint compared to rider-seated editions and they offer a safe driver platform. Rider-Seated Tow Tractors Rider-seated tow tractors are similar to stand-in models except they offer a seated platform for the operator. Rider-seated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. Reducing rider fatigue, the rider-seated models deliver more efficiency. Heavy Duty Tow Tractors The pushback concept is commonly used in aviation for cargo and large passenger planes. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. Heavy-duty tow tractors are known as pushback tugs or pushback tractors complete this task. Pushback tractors are designed with a low

profile design to enable them to move under the aircraft's nose in order to attach to the aircraft. Because of the added heavy weight of the aircraft, these tow tractors must be heavy enough to retain enough traction on the ground in order to move the aircraft. A common tractor for moving large aircraft can weigh in up to fifty-four tons. Their driver's cab has the ability to be lowered and raised for increased visibility during reversing. While the vehicle is referred to as a pushback tug or pushback tow tractor, it is also used to tow aircraft in areas where taxiing the aircraft is not practical or safe, such as moving large aircraft in and out of maintenance hangars. The pushback tow tractors come in two subtypes, the towbarless and the conventional.

Conventional Pushback Tow Tractors These units use a tow bar to attach the tug to the nose landing gear on the aircraft. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. The tow bar that attaches to the tug can pivot vertically and laterally. Acting like a giant lever, the tow bar can rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. On heavy towbars for large aircrafts, the towbar rides on its own wheels when not connected to an aircraft. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor.

Towbarless Pushback Tow Tractors Towbarless tractors work without a towbar and scoop up the aircrafts' nose landing gear to lift it off of the ground instead. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.